



CAMBRIAN SLATE

TECHNICAL DATA

Size (overall)	300 x 336mm
Minimum Pitch and Headlap	15° at 75mm headlap / 25° at 50mm headlap (The minimum pitch is based on a maximum rafter length of 10 metres. For rafter lengths greater than this, please contact the Technical Solutions Hotline on 03708 702595)
Maximum Pitch (subject to fire resistance requirements above 69°)	90°
Minimum Headlap	50mm
Maximum Headlap	90mm
Minimum Gauge/Batten Spacing	210mm
Maximum Gauge/Batten Spacing	below 25° 225mm / 25° and over 250mm
Hanging Length (approx)	294mm
Cover (all figures are net and do not allow for wastage)	
Linear cover of 1 slate	300mm
Covering capacity	14.8 slates/m ² at 225mm gauge / 13.3 slates/m ² at 250mm gauge
Weight	18kg/m ² at 225mm gauge / 17kg/m ² at 250mm gauge
per pallet, including pallet (approx.)	0.76 tonnes
per 1000	1.24 tonnes
Battens Required (at max. gauge)	4.0m/m ²
Batten Size	
Rafter centres up to 450mm	38 x 25mm
Rafter centres up to 600mm	50 x 25mm
Fixing Clips	Eaves, Verge & Slate Clips
Nail Size for Slates [#]	30 x 2.65mm (S/S)
Pallet Quantities	Slates per pallet 600 / Slates per pack 10 / Packs per pallet 60

[#](S/S) Stainless Steel Annular ring shanked