

CATHEDRAL CLAY PANTILE

TECHNICAL DATA

Size (overall)	411 x 265mm
Minimum Pitch and Headlap	22.5° at 61mm headlap / 30° at 51mm headlap
Maximum Pitch (subject to fixing specification)	90°
Maximum Headlap	71mm
Minimum Gauge/Batten Spacing	340mm
Maximum Gauge/Batten Spacing	below 30° 350mm / 30° and over 360mm
Hanging Length (approx.)	358mm
Cover (all figures are net and do not allow for wastage)	
Linear cover of 1 tile	225mm
Covering capacity	12.7 tiles/m ² at 350mm gauge / 12.3 tiles/m ² at 360mm gauge
Weight	39kg/m ² at 350mm gauge / 38kg/m ² at 360mm gauge
per pallet, including pallet (approx.)	0.92 tonnes
per 1000	3.10 tonnes
Battens Required (at max. gauge)	2.74m/m ²
Batten Size	
Rafter centres up to 450mm	38 x 25mm
Rafter centres up to 600mm	50 x 25mm
Nail Size for Tiles #	included with tile 60 x 2.65mm (S/S)
Pallet Quantities	Tiles per pallet 288 / Tiles per pack 6 / Packs per pallet 48

#(S/S) Stainless Steel Annular ring shanked nail with neoprene washer