

Declaration of Performance
No. 004 – Monier Redland Limited

1. Unique identification code of the product-type:
Underlays
2. Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4) of the CPR:
Spirtech 250, Spirtech 400, Spirtech 400 2S, Veltitech 145
3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:
Underlays for discontinuous roofing and wall cladding
4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11(5):
**Monier Redland Limited, Spectrum House, Beehive Ring Road, Gatwick, Crawley, RH6 0LG
Registered No 407552 England**
5. Where applicable, name and contact address of the authorised representative whose mandate covers the task specified in Article 12(2):
Not Applicable
6. System or systems of assessment and verification of constancy of performance of the construction product as set out in CPR, Annex V:
System 3 applies to this product
7. In case of the declaration of performance concerning a construction product covered by a harmonised standard:
BS EN 13859-1
8. In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued:
Not applicable.

9. Declared Performance


Table 9.1 Underlays for discontinuous roofing and wall cladding

Essential characteristics	Performance	Harmonised technical specification
Reaction to fire	E	BS EN 13859-1: 2014
Resistance to water penetration	W1	
Tensile strength N/50mm (long/trasv)	Spirtech 250 – (450/390) Spirtech 400 & 400 2S – (550/500) Veltitech 145 – (270/240)	
Resistance to tearing N (long/trasv)	Spirtech 250 – (340/360) Spirtech 400 & 400 2S – (450/450) Veltitech 145 – (180/180)	
Flexibility at low temperature (pliability)	Spirtech 250, -20°C Spirtech 400 & 400 2S, -25°C Veltitech 145, -20°C	
Artificial ageing behavior, concerning - resistance to water penetration - tensile strength N/50mm (long/trasv)	W1 Spirtech 250 – (400/340) Spirtech 400 & 400 2S – (500/440) Veltitech 145 – (240/210)	

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.

The declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:



.....

(signature)

A Dennis, Country Manager
Monier Redland Limited
Spectrum House, Beehive Ring Road, Gatwick, Crawley, RH6 0LG

30th September 2014