

DUOPLAIN RIDGES (incl. Vents & Vent Terminals) (NON-Sarking) - RIDGE BATTEN HEIGHT, AND TOP TILING BATTEN DISTANCE FROM APEX										
Ridge Battens 38mm Wide			Top Tiling Battens 50x25mm				Ridge Tiles: - Half Round			
RIDGE: - DIM: -	Mortar Bedded *		Dry *		DryVent *		Rapid		Rapid Vented	
	Ridge Batten Height (mm)	Top Batten Distance (mm)	Ridge Batten Height (mm)	Top Batten Distance (mm)	Ridge Batten Height (mm)	Top Batten Distance (mm)	Ridge Batten Height (mm)	Top Batten Distance (mm)	Ridge Batten Height (mm)	Top Batten Distance (mm)
PITCH										
22.5°	50	40	50	40	50	40	50	40	50	40
25.0°	50	40	50	40	50	40	50	40	50	40
27.5°	50	40	50	40	50	40	50	40	50	40
30.0°	50	40	50	40	50	40	50	40	50	40
32.5°	25	40	50	40	50	40	50	40	50	40
35.0°	25	40	25	40	25	40	50	40	50	40
37.5°	25	40	25	40	25	40	25	40	50	40
40.0°	25	40	25	40	25	40	25	40	50	40
42.5°	25	40	25	40	25	40	25	40	25	40
45.0°	25	40	25	40	25	40	25	40	25	40
47.5°	25	40	25	40	25	40	25	40	25	40
50.0°	25	40	25	40	25	40	25	40	25	40
52.5°	25	40	25	40	25	40	C25	40	25	40
55.0°	25	40	25	40	25	40	X	X	25	40
57.5°	25	40	25	40	25	40	X	X	X	X
60.0°	C25	40	25	40	25	40	X	X	X	X
62.5°	C25	80	X	X	X	X	X	X	X	X
65.0°	C25	C80	X	X	X	X	X	X	X	X
67.5°	C25	C110	X	X	X	X	X	X	X	X
70.0°	C25	C110	X	X	X	X	X	X	X	X
72.5° *	C25	C140	X	X	X	X	X	X	X	X
75.0° *	C25	C170	X	X	X	X	X	X	X	X
76.5° *	C25	C200	X	X	X	X	X	X	X	X
77.5° *	C25	C220	X	X	X	X	X	X	X	X
78.5° *	C25	C240	X	X	X	X	X	X	X	X
79.5° *	C25	C255	X	X	X	X	X	X	X	X
80.0° *	C25	C270	X	X	X	X	X	X	X	X

Pitches Between Those on Table: - Use the **Greater** Distance and/or Height: -

Eg: - Rapid Vented at 42.0°: Ridge batten height = 50mm.  
Mortar Bedded at 60.5°: Top batten distance = 80mm

\* Mortar Bedded, Dry & DryVent Details apply also to Ridge Vents & Ridge Vent Terminals

X: - Not available  
**Bold**: - Maximum pitch without modification to rafters at apex  
C: - Available with tops of rafters suitably cut at apex  
\* : - Pitch range for tile currently 25° to 70° inclusive