



FONTENELLE INTERLOCKING CLAY PLAIN TILE

TECHNICAL DATA

Size (overall)	350 x 244mm
Minimum Pitch (The minimum pitch is 15° in certain circumstances. The minimum pitch is based on a maximum rafter length of 10 metres. For rafter lengths greater than this and related queries, please contact the Technical Solutions on 03708 702595)	20°
Maximum Pitch (subject to fixing specification)	90°
Minimum Headlap	95mm
Maximum Headlap	110mm
Minimum Gauge/Batten Spacing	240mm
Maximum Gauge/Batten Spacing	255mm
Hanging Length (approx.)	321mm
Cover (all figures are net and do not allow for wastage) Linear cover of 1 tile	200mm
Covering capacity	19.6 tiles/m ² (at 255mm gauge)
Weight per pallet, including pallet (approx.) per 1000	52kg/m ² (at 255mm gauge) 1.13 tonnes 2.65 tonnes
Battens Required (at max. gauge)	3.92m/m ²
Batten Size Rafter centres up to 450mm Rafter centres up to 600mm	38 x 25mm 50 x 25mm
Nail Size for Tiles* (Depending on fixing specification)	55 x 2.65mm (S/S)
Pallet Quantities	Tiles per pallet 420 / Tiles per pack 60 / Packs per pallet 7

* (S/S) Stainless Steel Ring Shank