

# LANDMARK DOUBLE PANTILE

## TECHNICAL DATA

<b>Size</b> (overall)	418 x 332mm
<b>Minimum Pitch and Headlap</b>	15° at 100mm headlap 17.5° at 75mm headlap
<b>Maximum Pitch</b> (subject to fixing specification)	90°
<b>Maximum Headlap</b>	125mm
<b>Minimum Gauge/Batten Spacing</b>	293mm
<b>Maximum Gauge/Batten Spacing</b>	below 17.5° 318mm / 17.5° and over 343mm
<b>Hanging Length</b> (approx.)	397mm
<b>Cover</b> (all figures are net and do not allow for wastage)	
Linear cover of 1 tile	300mm
Covering capacity	10.5 tiles/m <sup>2</sup> at 318mm gauge / 9.7 tiles/m <sup>2</sup> at 343mm gauge
<b>Weight</b>	50kg/m <sup>2</sup> at 318mm gauge / 47kg/m <sup>2</sup> at 343mm gauge
per pallet, including pallet (approx.)	1.02 tonnes
per 1000	4.80 tonnes
<b>Battens Required</b> (at max. gauge)	2.92m/m <sup>2</sup>
<b>Batten Size</b>	
Rafter centres up to 450mm	38 x 25mm
Rafter centres up to 600mm	50 x 25mm
<b>Fixing Clips</b>	Eaves, Verge & Tile Clips
<b>Nail Size for Tiles</b> #	70 x 3.75mm (A/A)
<b>Pallet Quantities</b>	Tiles per pallet 210 / Tiles per pack 35 / Packs per pallet 6

#(A/A) Aluminium Alloy