

LANDMARK DOUBLE ROMAN

TECHNICAL DATA

Size (overall)	418 x 330mm
Minimum Pitch and Headlap	17.5° at 100mm headlap 22.5° at 75mm headlap
Maximum Pitch (subject to fixing specification)	90°
Maximum Headlap	125mm
Minimum Gauge/Batten Spacing	293mm
Maximum Gauge/Batten Spacing	below 22.5° 318mm 22.5° and over 343mm
Hanging Length (approx.)	397mm
Cover (all figures are net and do not allow for wastage)	
Linear cover of 1 tile	300mm
Covering capacity	10.5 tiles/m ² at 318mm gauge / 9.7 tiles/m ² at 343mm gauge
Weight	45kg/m ² at 318mm gauge / 42kg/m ² at 343mm gauge
per pallet, including pallet (approx.)	1.05 tonnes
per 1000	4.30 tonnes
Battens Required (at max. gauge)	2.92m/m ²
Batten Size	
Rafter centres up to 450mm	38 x 25mm
Rafter centres up to 600mm	50 x 25mm
Fixing Clips	Eaves, Verge & Tile Clips
Nail Size for Tiles #	60 x 3.35mm (A/A)
Pallet Quantities	Tiles per pallet 240 / Tiles per pack 40 / Packs per pallet 6

#(A/A) Aluminium Alloy