



WESTMINSTER SLATE

An elegant natural clay slate offering savings in both materials and labour. Simple and quick to install.



KEY ADVANTAGES

- Engineered clay slate with hidden interlock
- Tapered leading edge for an exceptionally thin appearance
- For pitches as low as 17.5°

TECHNICAL DATA

Size (overall)		480 × 326mm
Minimum Pitch		17.5°
	on a maximum rafter length of 10 plutions Hotline on 03708 702595	metres. For rafter lengths greater than this,
Maximum Pitch (subject	to fixing specification)	90°
Minimum Headlap		110mm
Maximum Headlap		140mm
Minimum Gauge/Batte	en Spacing	340mm
Maximum Gauge/Batt	en Spacing	370mm
Hanging Length (approx)	452mm
Cover (all figures are net ar	d do not allow for wastage)	
Linear cover of 1 slate		280mm
Covering capacity		9.7 slates/m² at 370mm gauge
Weight		47.5kg/m² at 370mm gauge
per pallet, including pal	let (approx.)	1.05 tonnes
per 1000		4.9 tonnes
Battens Required (at m	ax. gauge)	2.7m/m ²
Batten Size		
Rafter centres up to 450mm		38 × 25mm
Rafter centres up to 600mm		50 × 25mm
Fixing Clips		Eaves, Verge & Slate Clips
Nail Size for Slates#		55 x 2.65mm (S/S)
Pallet Quantities	Slates per pallet 210 / S	Slates per pack 5 / Packs per pallet 42


^{#(}S/S) Stainless Steel Annular ring shanked

FITTINGS & ACCESSORIES

Hip	Rosemary Third Round Hip Clay Universal Angle Hip Dry Hip System Continuous Hip System
Valley	125 GRP Valley Dry Valley
Ridge	Rosemary Half Round Ridge Clay Universal Angle Ridge
Ventilation Systems	RedVent EavesVent RedVent 25 Over-Fascia Vent Rapid Eaves Vent Top Edge Abutment Ventilation DryVent Ridge Continuous Ridge System Uni-Vent Rapid Ridge/Hip 8.8k ThruVent Tile

CLAY UNIVERSAL ANGLE RIDGE AND HIPTILES

Both ridges and hips are available in Black and Rec



CLAY HALF ROUND RIDGE AND HIP TILES

Both ridges and hips are available in Red and Light Mixed Brindle





COLOURS







80 Cardinal Red