

REGENT

TECHNICAL DATA

Size (overall)	418 x 332mm
Minimum Pitch and Headlap	
Through coloured	12.5°* at 100mm headlap / 17.5° at 75mm headlap
Granular	22.5° at 100mm headlap / 30° at 75mm headlap
Maximum Pitch (subject to fixing specification)	90°
Maximum Headlap	125mm
Minimum Gauge/Batten Spacing	293mm
Maximum Gauge/Batten Spacing	
Through coloured	below 17.5° at 318mm / 17.5° and over 343mm
Granular	below 30° at 318mm / 30° and over 343mm
Hanging Length (approx.)	397mm
Cover (all figures are net and do not allow for wastage)	
Linear cover of 1 tile	300mm
Covering capacity	10.5 tiles/m ² at 318mm gauge / 9.7 tiles/m ² at 343mm gauge
Weight	48kg/m ² at 318mm gauge / 45kg/m ² at 343mm gauge
per pallet, including pallet (approx.)	1.22 tonnes
per 1000	4.60 tonnes
Battens Required (at max. gauge)	2.92m/m ²
Batten Size	
Rafter centres up to 450mm	38 x 25mm
Rafter centres up to 600mm	50 x 25mm
Fixing Clips	Eaves, Verge & Tile Clips
Nail Size for Tiles #	75 x 3.35mm (A/A)
Pallet Quantities	Tiles per pallet 252 / Tiles per pack 42 / Packs per pallet 6

* Minimum pitch is 15° if roof contains valleys # (A/A) Aluminium Alloy