

WESTMINSTER SLATE

TECHNICAL DATA

Size (overall)	480 x 326mm
Minimum Pitch	17.5°
(The minimum pitch is based on a maximum rafter length of 10 metres. For rafter lengths greater than this, please contact the Technical Solutions Hotline on 03708 702595)	
Maximum Pitch (subject to fixing specification)	90°
Minimum Headlap	110mm
Maximum Headlap	140mm
Minimum Gauge/Batten Spacing	340mm
Maximum Gauge/Batten Spacing	370mm
Hanging Length (approx)	452mm
Cover (all figures are net and do not allow for wastage)	
Linear cover of 1 slate	280mm
Covering capacity	9.7 slates/m ² at 370mm gauge
Weight	47.5kg/m ² at 370mm gauge
per pallet, including pallet (approx.)	1.05 tonnes
per 1000	4.9 tonnes
Battens Required (at max. gauge)	2.7m/m ²
Batten Size	
Rafter centres up to 450mm	38 x 25mm
Rafter centres up to 600mm	50 x 25mm
Fixing Clips	Eaves, Verge & Slate Clips
Nail Size for Slates [#]	55 x 2.65mm (S/S)
Pallet Quantities	Slates per pallet 210 / Slates per pack 5 / Packs per pallet 42

[#](S/S) Stainless Steel Annular ring shanked