

PITCH RANGE AND RIDGE BATTEN HEIGHT FOR DRY AND DRYVENT RIDGE SYSTEMS (38mm WIDTH)																						Rev: C		
Profile	Rafter Pitch (Degrees)																							
	12.5	15	17.5	20	22.5	25	27.5	30	32.5	35	37.5	40	42.5	45	47.5	50	52.5	55	57.5	60	62.5	65	67.5	70
Half Round	Batten Height (mm)																							
Landmark Double Pantile ^A	-	100	100	75	75	75	75	75	75	50	50	50	50	50	50	50	50	-	-	-	-	-	-	-
Grovebury ^A	-	100	100	75	75	75	75	75	75	50	50	50	50	50	50	50	50	-	-	-	-	-	-	-
50 Double Roman ^A	-	-	75	75	75	75	50	50	50	50	50	25	25	25	25	25	-	-	-	-	-	-	-	
Regent ^B	100	100	100	100	75	75	75	75	75	50	50	50	50	50	50	50	50	-	-	-	-	-	-	-
Renown ^A	-	-	75	75	50	50	50	50	50	25	25	25	25	25	25	25	25	-	-	-	-	-	-	-
Norfolk Pantile ^B	-	-	100	100	75	75	75	75	75	50	50	50	50	50	50	50	50	-	-	-	-	-	-	-
Cambrian	-	50	50	50	50	25	25	25	25	25	25	25	25	25	25	25	25	-	-	-	-	-	-	-
Saxon	-	-	-	-	-	50	50	50	50	25	25	25	25	25	25	25	25	25	-	-	-	-	-	-
Landmark Slate	-	-	-	-	50	50	50	50	25	25	25	25	25	25	25	25	25	25	-	-	-	-	-	-
Richmond	-	-	-	-	50	50	50	50	25	25	25	25	25	25	25	25	25	25	-	-	-	-	-	-
Stonewold II	-	-	75	50	50	50	50	50	50	25	25	25	25	25	25*	-	-	-	-	-	-	-	-	-
Mini Stonewold	-	-	75	50	50	50	50	50	50	25	25	25	25	25	25	25	25	25	-	-	-	-	-	-
Plain Tile	-	-	-	-	-	-	-	-	-	50	25	25	25	25	25	25	25	25	25	25	25	25	-	-
Heathland	-	-	-	-	-	-	-	-	-	50	25	25	25	25	25	25	25	25	25	25	25	25	-	-
Downland	-	-	-	-	-	-	-	-	-	50	25	25	25	25	25	25	25	25	25	25	25	25	-	-
DuoPlain	-	-	-	-	-	50	50	50	50	25	25	25	25	25	25	25	25	25	25	25	25	-	-	-
Del Carmen (Standard) Natural Slate (ns)	-	-	-	-	50	25	25	25	25	25	25	25	25	25	25	25	-	-	-	-	-	-	-	-
Universal Angle	Batten Height (mm)																							
Cambrian	-	50	50	50	50	25	25	25	25	25	25	25	25	25	25	25	25**	-	-	-	-	-	-	-
Saxon	-	-	-	-	-	50	50	50	50	25	25	25	25	25	25	25	25	25	-	-	-	-	-	-
Landmark Slate	-	-	-	-	50	50	50	50	50	25	25	25	25	25	25	25	25	25	-	-	-	-	-	-
Richmond	-	-	-	-	50	50	50	50	50	25	25	25	25	25	25	25	25	25	-	-	-	-	-	-
Stonewold II	-	-	75	75	50	50	50	50	50	25	25	25	25	25	25*	-	-	-	-	-	-	-	-	-
Mini Stonewold	-	-	75	75	50	50	50	50	50	25	25	25	25	25	25	25	25	25	-	-	-	-	-	-
Plain Tile	-	-	-	-	-	-	-	-	-	50	25	25	25	25	25	25	25	25	25	25	25	-	-	-
Del Carmen (Standard) Natural Slate (ns)	-	-	-	-	50	25	25	25	25	25	25	25	25	25	25	-	-	-	-	-	-	-	-	-
Rosemary Half Round	Batten Height (mm)																							
Cambrian	-	75	75	75	75	75	75	50	50	50	50	25	25	25	25	25	25	25	25	-	-	-	-	-
Saxon	-	-	-	-	-	75	75	75	75	75	50	50	50	50	50	50	50	50	50	50	50	50	-	-
Landmark Slate	-	-	-	-	75	75	75	75	75	75	50	50	50	50	25	25	25	25	25	25	25	25	-	-
Richmond	-	-	-	-	75	75	75	75	75	75	50	50	50	50	25	25	25	25	25	25	25	25	-	-
Rosemary Clay Plain Tile	-	-	-	-	-	-	-	-	-	75	75	75	50	50	50	50	50	25	25	25	25	25	25	
Del Carmen (Standard) Natural Slate (ns)	-	-	-	-	75	75	50	50	50	50	25	25	25	25	25	25	25	25	-	-	-	-	-	

* 44° Maximum Pitch

(ns): Natural Slate - Figures shown for pre-holed stock product. Minimum pitch 20° with slates holed to specification. Pitch range depends upon exposure level. Higher pitches available with slates holed to specification and/or special trimmed rafter detail. Riverstone details not yet available. See full Natural Slate tables for full details of top slate size and hole position, batten gauges, exposure levels and the like.

Pitches Between Those Shown: -
Use taller Ridge Batten Height

** Trim 10mm off truss apex.

TOP BATTEN DISTANCE FROM APEX

Slate	Stonewold II	90mm
	Cambrian	30mm
	All Other Slates	60mm
	Natural Slate	Contact Technical
Profile	All Tiles:	55mm (Except ^A & ^B)
	^A = At Over 45°:	45mm
	^B = At Over 40°:	40mm
Plain	Rosemary Top	35mm
	2nd Top	75mm
	Concrete	70mm
	DuoPlain	40mm