

# FENLAND PANTILE

## TECHNICAL DATA

<b>Size</b> (overall)	381 × 227mm
<b>Minimum Pitch and Headlap</b>	17.5° at 100mm headlap / 22.5° at 75mm headlap
<b>Maximum Pitch</b> (subject to fixing specification)	90°
<b>Maximum Headlap</b>	125mm
<b>Minimum Gauge/Batten Spacing</b>	256mm
<b>Maximum Gauge/Batten Spacing</b>	below 22.5° 281mm 22.5° and over 306mm
<b>Hanging Length</b> (approx.)	362mm
<b>Cover</b> (all figures are net and do not allow for wastage)	
Linear cover of 1 tile	200mm
Covering capacity	17.8 tiles/m <sup>2</sup> at 281mm gauge / 16.3 tiles/m <sup>2</sup> at 306mm gauge
<b>Weight</b>	49kg/m <sup>2</sup> at 281mm gauge / 45kg/m <sup>2</sup> at 306mm gauge
per pallet, including pallet (approx.)	0.98 tonnes
per 1000	2.75 tonnes
<b>Battens Required</b> (at max. gauge)	3.26m/m <sup>2</sup>
<b>Batten Size</b>	
Rafter centres up to 450mm	38 × 25mm
Rafter centres up to 600mm	50 × 25mm
<b>Fixing Clips</b>	Eaves, Verge & Tile Clips
<b>Nail Size for Tiles</b> #	45 × 3mm (A/A)
<b>Pallet Quantities</b>	Tiles per pallet 336 / Tiles per pack 42 / Packs per pallet 8

#(A/A) Aluminium Alloy