

# LANDMARK 10 SLATE

## TECHNICAL DATA

<b>Size</b> (overall)	418 x 330mm
<b>Minimum Pitch and Headlap</b>	17.5° at 100mm headlap / 22.5° at 75mm headlap (The minimum pitch is based on a maximum rafter length of 10 metres. For rafter lengths greater than this, please contact the Technical Solutions Hotline on 03708 702595)
<b>Maximum Pitch</b> (subject to fixing specification)	90°
<b>Minimum Headlap</b>	75mm
<b>Maximum Headlap</b>	125mm
<b>Minimum Gauge/Batten Spacing</b>	293mm
<b>Maximum Gauge/Batten Spacing</b>	below 22.5° 318mm / 22.5° and over 343mm
<b>Hanging Length</b> (approx.)	395mm
<b>Cover</b> (all figures are net and do not allow for wastage)	
Linear cover of 1 slate	300mm
Covering capacity	10.5 slates/m <sup>2</sup> at 318mm gauge / 9.7 slates/m <sup>2</sup> at 343mm gauge
<b>Weight</b>	49kg/m <sup>2</sup> at 318mm gauge / 46kg/m <sup>2</sup> at 343mm gauge
per pallet, including pallet (approx.)	1.00 tonnes
per 1000	4.7 tonnes
<b>Battens Required</b> (at max. gauge)	2.92m <sup>2</sup>
<b>Batten Size</b>	
Rafter centres up to 450mm	38 x 25mm
Rafter centres up to 600mm	50 x 25mm
<b>Fixing Clips</b>	Eaves, Verge & Slate Clips
<b>Nail Size for Slates<sup>#</sup></b>	45 x 3mm (A/A) 45 x 3.35mm (S/S)
<b>Pallet Quantities</b>	Slates per pallet 210 / Slates per pack 35 / Packs per pallet 6

<sup>#</sup>(S/S) Stainless Steel Annular ring shanked (A/A) Aluminium Alloy