



MOCKBOND RICHMOND 10 SLATE

TECHNICAL DATA

Size (overall)	418 x 330mm
Minimum Pitch and Headlap	17.5° at 100mm headlap / 27.5° at 75mm headlap (The minimum pitch is based on a maximum rafter length of 10 metres. For rafter lengths greater than this, please contact the Technical Solutions Hotline on 03708 702595)
Maximum Pitch (subject to fixing specification)	90°
Minimum Headlap	75mm
Maximum Headlap	125mm
Minimum Gauge/Batten Spacing	293mm
Maximum Gauge/Batten Spacing	below 27.5° 318mm / 27.5° and over 343mm
Hanging Length (approx.)	395mm
Cover (all figures are net and do not allow for wastage)	
Linear cover of 1 slate	300mm
Covering capacity	10.5 slates/m ² at 318mm gauge / 9.7 slates/m ² at 343mm gauge
Weight	48kg/m ² at 318mm gauge / 45kg/m ² at 343mm gauge
per pallet, including pallet (approx.)	1.02 tonnes
per 1000	4.60 tonnes
Battens Required (at max. gauge)	2.92m/m ²
Batten Size	
Rafter centres up to 450mm	38 x 25mm
Rafter centres up to 600mm	50 x 25mm
Fixing Clips	Eaves, Verge & Slate Clips
Nail Size for Slates [#]	45 x 3mm (A/A) 45 x 3.35mm (S/S)
Pallet Quantities	Slates per pallet 210 / Slates per pack 35 / Packs per pallet 6

*All weights nominal [#](S/S) Stainless Steel Annular ring shanked (A/A) Aluminium Alloy