

OLD HOLLOW CLAY PANTILE

TECHNICAL DATA

Size (overall)	343 x 242mm
Minimum Pitch and Headlap	30° at 48mm headlap / 35° at 38mm headlap
Maximum Pitch (subject to fixing specification)	90°
Minimum Gauge/Batten Spacing	295mm
Maximum Gauge/Batten Spacing	below 35° 295mm / 35° and over 305mm
Hanging Length (approx.)	310mm
Cover (all figures are net and do not allow for wastage)	
Linear cover of 1 tile	below 35° 206mm / 35° and over 202mm
Covering capacity	16.8 tiles/m ² at 295mm gauge / 16.2 tiles/m ² at 305mm gauge
Weight	
37kg/m ² at 295mm gauge / 36kg/m ² at 305mm gauge	
per pallet, including pallet (approx.)	0.76 tonnes
per 1000	2.20 tonnes
Battens Required (at max. gauge)	below 35° 3.39m ² / 35° and over 3.28m ²
Batten Size	
Rafter centres up to 450mm	38 x 25mm
Rafter centres up to 600mm	50 x 25mm
Nail Size for Tiles [#]	55 x 2.65mm (S/S)
Pallet Quantities	Tiles per pallet 336 / Tiles per pack 6 / Packs per pallet 56

[#](S/S) Stainless Steel Annular ring shanked