




PLAIN TILE

A cross-cambered concrete tile with a traditional appearance that's easy to fix and robust enough to withstand the worst of the British weather.



Plain Tiles, Breckland Black,
Alvaston Hall, Cheshire

WWW.REDLAND.CO.UK/PLAINTILE



PLAIN TILE

Available in a range of fourteen natural shades, granular; through-coloured and acrylic coated, to match any roofing environment.

KEY ADVANTAGES

- Versatile concrete tile with wide scope for a variety of roofing effects
- Quick and easy to lay
- Smooth, coated and sanded finishes to blend with every regional roofing style

TECHNICAL DATA

Size (overall)	266 x 165mm
Minimum Pitch	35°
Maximum Pitch (subject to fixing specification)	90°
Minimum Headlap	Below 90° 65mm / at 90° 35mm
Maximum Headlap	88mm
Minimum Gauge/Batten Spacing	88mm
Maximum Gauge/Batten Spacing	below 90° 100mm / at 90° 115mm
Hanging Length (approx.)	246mm
Cover (all figures are net and do not allow for wastage)	
Linear cover of 1 tile	165mm
Covering capacity	below 90° 60 tiles/m ² / at 90° 52 tiles/m ²
Weight	below 90° 75kg/m ² / at 90° 65kg/m ²
per pallet, including pallet (approx.)	1.01 tonnes
per 1000	1.25 tonnes
Battens Required (at max. gauge)	below 90° 10.0m/m ²
Batten Size	
Rafter centres up to 600mm	38 x 25mm
Fixing Clips	Top Tile Clips
Nail Size for Tiles*	40 x 2.65mm (A/A)
Pallet Quantities	Tiles per pallet 768 / Tiles per pack 16 / Packs per pallet 48

* (A/A) Aluminium Alloy

FITTINGS & ACCESSORIES

Ornamental Tile	Club Tiles
Angles	External Angles
Hip	Universal Bonnet Hip Third Round Hip Baby Ridge Dry Hip Rapid Hip
Valley	Universal Valley Tile 125 GRP Valley Dry Valley
Ridge	Half Round Ridge Half Round Monoridge
Ventilation Systems	RedVent EavesVent RedVent 25 Over-Fascia Vent Rapid EavesVent Top Edge Abutment Ventilation DryVent Ridge DryVent Monoridge Continuous Ridge System Uni-Vent Rapid Ridge/Hip RedLine Vent Tile Rapid RoofVent 4.5k ThruVent Tile

COLOURS

