



# POSTEL CLAY TILE

## TECHNICAL DATA

<b>Size</b> (overall)	315 x 230mm
<b>Minimum Pitch and Headlap</b>	20° at 70mm headlap
<b>Maximum Pitch</b> (subject to fixing specification)	90°
<b>Minimum Gauge/Batten Spacing</b>	235mm
<b>Maximum Gauge/Batten Spacing</b>	245mm
<b>Hanging Length</b> (approx.)	285mm
<b>Cover</b> (all figures are net and do not allow for wastage)	
Linear cover of 1 tile	200mm
Covering capacity	20.4 tiles/m <sup>2</sup>
<b>Weight</b>	41kg/m <sup>2</sup>
per pallet, including pallet (approx.)	1.22 tonnes
per 1000	2.00 tonnes
<b>Battens Required</b> (at max. gauge)	4.08kg/m <sup>2</sup>
<b>Batten Size</b>	
Rafter centres up to 450mm	38 x 25mm
Rafter centres up to 600mm	50 x 25mm
<b>Nail Size for Tiles</b> #	45 x 3.35mm (S/S)
<b>Pallet Quantities</b>	Tiles per pallet 600 / Tiles per pack 8 / Packs per pallet 75

#(S/S) Stainless Steel Annular ring shanked