




POSTEL CLAY TILE

Emulating the Courtrai tile, which was imported into the UK from Belgium between the world wars due to a lack of indigenous supply at the time.



Postel Clay Tile, Brindle, Private House

WWW.REDLAND.CO.UK/POSTEL



POSTEL CLAY TILE

A tile particularly popular in the south-east for domestic reroofing, it replicates the shape of the 'Courtrai' tile, with guaranteed weathertightness down to 20°.

KEY ADVANTAGES

- Clay single Roman interlocking tile
- Classic tile that maintains the heritage look of an area

TECHNICAL DATA

Size (overall)	315 x 230mm
Minimum Pitch and Headlap	20° at 70mm headlap
Maximum Pitch (subject to fixing specification)	90°
Minimum Gauge/Batten Spacing	235mm
Maximum Gauge/Batten Spacing	245mm
Hanging Length (approx.)	285mm
Cover (all figures are net and do not allow for wastage)	
Linear cover of 1 tile	200mm
Covering capacity	20.4 tiles/m ²
Weight	41kg/m ²
per pallet, including pallet (approx.)	1.22 tonnes
per 1000	2.00 tonnes
Battens Required (at max. gauge)	4.08kg/m ²
Batten Size	
Rafter centres up to 450mm	38 x 25mm
Rafter centres up to 600mm	50 x 25mm
Nail Size for Tiles #	45 x 3.35mm (S/S)
Pallet Quantities	Tiles per pallet 600 / Tiles per pack 8 / Packs per pallet 75

#(S/S) Stainless Steel Annular ring shanked

FITTINGS & ACCESSORIES

Hip	Third Round Hip
Valley	125 GRP Valley Dry Valley
Ridge	Half Round Ridge
Ventilation Systems	RedVent EavesVent RedVent 25 Over-Fascia Vent Rapid Eaves Vent Continuous Ridge System Uni-Vent Rapid Ridge/Hip 4.5k ThruVent Tile

COLOURS



82 Brindle



Postel Clay Tile, Brindle,
Mell Homes, Fosters Croft